



### ARESTA Scaff

Elasticated lanyard with snaphook & scaffold hooks

Very popular elasticated webbing lanyard for the scaffolding, construction industry, plant maintenance, roof maintenance. Twin legs ensure the worker is always attached at all times whilst moving from anchor to anchor. Includes a carabiner at the harness end and scaff-hooks at the anchorage end. Stay safe at all times with a double lanyard for continuous attachment to anchor points, providing a fool proof fall arrest system

- Total extended length is 2m.
- The shock absorber will tear to absorb the energy in the event of a fall
- carabiner and scaff-hooks rated to 20kN.
- Do not remove the yellow cover as this protects the shock absorber from environmental damage

### Codes

Single AR-03909

Twin AR-03703

EN 355 EN359

| Ref               | Model    | Size | Weight | Rated to | Breaking Strength | Material                            | Standards        |
|-------------------|----------|------|--------|----------|-------------------|-------------------------------------|------------------|
|                   |          |      | g      | KG       |                   |                                     |                  |
| Single 2m lanyard | AR-03909 | 2m   |        | 140kg    | 25KN              | Polyester Webbing<br>Steel Hardware | EN 355<br>EN 359 |
| Twin 2m Lanyard   | AR-03703 | 2m   |        | 140kg    | 25KN              | Polyester Webbing<br>Steel Hardware | EN 355<br>EN 359 |

# CE 0082