


ALFRA ROTABEST® – RB 80 B

B-LINE



MADE IN GERMANY



RB 80 B

Core drill dimensions	Ø 12.0 - 80.0 mm / Ø 20.0 - 50.0 mm (cutting depth 110 mm)
Cutting depth	50.0 mm / 110.0 mm
Twist drill	Ø 1.0 - 16.0 mm with drill chuck Up to Ø 32.0 mm with MT3 DIN 345
Counterboring	Ø 10 - 55.0 mm
Tapping	with tapping attachment: Up to M30
Arbors	MT3
Stroke	190 mm
Height adjustment	100 mm
4-speed gearbox Load speed	1. Step 110 rpm 2. Step 175 rpm 3. Step 245 rpm 4. Step 385 rpm
Power consumption	1,800 W
Voltage	230 V 50/60 Hz 110 V 50/60 Hz
Magnetic adhesion strength	16,000 N
Tool force (10 mm)	4,000 N
Magnetic base	92 x 220 mm
Weight	21.8 kg

Motor

Motor emergency stop	✓
Oil bath gearbox	✓
Mech. Slip clutch	✓

Slides

Infinitely adjustable	✓
Self-adjusting guide	✓

Operation

Soft-touch grips	✓
Membrane keyboard	✓
Holder for Allen key	✓
Cable length 5 m	✓

Magnet

Sensor/LED	✓
Metal rings	✓
Performance and weight optimisation	✓

Made in Germany

	✓
--	---

Scope of delivery

- Metal core drilling machine **RB 80 B**
- Coolant device
- MT3 tool holder with internal cooling
- Carrying case
- Drill spray
- Seat belt
- Operating Instructions
- **incl. 1 core drill free**

Prod.-No.

ALFRA Rotabest® RB 80 B	230 Volt	18481
ALFRA Rotabest® RB 80 B	110 Volt	18481.110