

Metal Cutter XGT®

CS002GZ01

40Vmax • 185 mm • 3 500 min⁻¹



Technical specifications

Vibration Level, Cutting metal	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor), Cutting metal	1,5 m/s ²
Voltage XGT	✓
Nominal Battery Voltage	40 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	3500 min ⁻¹
Max. Cutting Depth at 90°	67 mm
Blade Diameter	185 mm
Bore Size (Arbor Diameter)	30 mm
Electronic brake	✓
Sound Power Level (L _{WA})	113 dB(A)
Sound Pressure Level (L _{pA})	102 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Product net weight	2,6 kg

EAN 0088381764988

Link to product - www.makita.com

User benefits

- Electronic soft start feature for smooth start ups
- Twin LED lights with pre-glow and afterglow feature illuminate the work area
- Brushless maintenance-free and long-life motor
- Electric brake for increased productivity and operator safety
- Brushless motor is electronically controlled to optimise battery energy use for longer run time per charge



Related products

■ Standard AC

164095-8
Parallel Guide



783203-8
Hex Wrench 5 Mm



821552-6
Makpac case (4)



■ Other

[User manual](#)

[Parts drawing](#)