

TECHNICAL DATA SHEET CPP

BASE MATERIALS & FEATURES

Florprotec CPP is a woven coated polypropylene sheeting. Flame retardant to either LPS1207 or to BSAU169 standard.

FLAME RETARDANT DETAILS

Loss Prevention Standard

Flame retardant to Loss Prevention Standard 1207(LPS1207)
CPP is also tested to British Standard BSAU169 (Method for determination of burning behaviour of interior materials) BSAU169 (ISO3795) – burning resistance requirements, flammability testing – pass.

STRENGTH

Tear and burst puncture test BS4303 – determination of the resistance to tearing of woven fabrics.
ISO2960 determination of burst resistance.

APPLICATIONS

General purpose floor protector (for all floor types) against site activity, interior fit-outs, decorating etc. Particularly suited to carpet protection as it resists 'creeping'. Widely used on vinyl, speciality resin and power float floors.

ADVANTAGES

- Exceptional tear strength and puncture resistance (Impossible to tear and puncture by hand)
- Safely protects floors from long term site activity
- Waterproof
- Light weight (200m2 roll weighs 20kg)
- 2m wide rolls makes for quick and easy fitting and removal
- White colour reflects available light, assisting on site visibility
- Single colour custom-print available
- Economical, high volume, low cost protector
- Textured anti-slip surface for good site safety in accordance with HSE guidelines

PRODUCT DETAILS

Code	CPP Grade FR Standard	Roll Size	Weight
M4 Florprotec®	CPP BSAU169	2m x 100m	20kg
M97 Florprotec®	CPP BSAU169	2m x 50m	9kg
M98 Florprotec®	CPP BSAU169	1m x 100m	9kg
M215 Florprotec®	CPP-FR LPS1207	2m x 100m	20kg

There are a number of ways of fixing the CPP to your flooring area, low tack tape, pins or Velcro tape. Please ask for information when ordering.

