

Angle Grinder XGT®

GA022GZ01

40Vmax • 115 mm • 3 000 – 8 500 min⁻¹



Technical specifications

Vibration Level, Disc Sanding	≤ 2,5 m/s ²
Vibration Level, Surface Grinding	5,5 m/s ²
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s ²
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s ²
Voltage XGT	✓
Nominal Battery Voltage	40 V
Max Output Power	1100 W
No load speed	3000 - 8500 min ⁻¹
Max. Depth of Cut	29 mm
Spindle Thread	M14
Bore Size (Arbor Diameter)	22,23 mm
Grinding Disc Diameter	115 mm
Anti-Restart Function (NVR Switch)	✓
Electronic brake	✓
AWS ready	✓
Sound Power Level (L _{WA})	92 dB(A)

User benefits

- Excellent in continuous heavy-duty work
- New tool-less wheel cover allows for fast and easy angle adjustment and installation/removal of wheel cover
- Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth
- Active Feedback sensing Technology (AFT) turns the motor off if rotation speed suddenly slows or wheel is forced to stop
- Electric brake for maximum productivity
- Brushless motor eliminates carbon brushes, enabling the Brushless motor to run cooler and more efficiently for longer life
- Soft grip provides increased comfort on the job
- Slide switch with lock-on for operator convenience
- Soft start suppresses start-up reaction for smooth start-ups and longer gear life
- Anti-restart function engineered to minimise motor start up when battery is inserted with switch locked on
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to product - www.makitauk.com



Related products

Standard AC

158237-4
Grip 36 complete



782423-1
Lock nut wrench 35



821552-6
Makpac case (4)



835E79-0
Inner tray (4)



A-80640
Grinding Wheel 115 X 6 Mm, Wa36N,



Optional AC

158237-4
Grip 36 complete



782423-1
Lock nut wrench 35



821552-6
Makpac case (4)



835E79-0
Inner tray (4)



Other

[User manual](#)

[Parts drawing](#)