




GUARD BOLLARD

ARCHITECTURAL BOLLARDS

Guard Architectural Bollards are stylish and robust. Available in 4 interchangeable heads. Ideal for walkways, entrance ways, drives and other small-area lighting applications where low mounting heights are desirable.



Features

- Attractive architectural Design
- Integrated 3 Hour Emergency
- CCT Selectable
- 5 Year Warranty
- Durable powder coat finish

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
GRD24A-DL-EM-CCT	Guard Bollard Dome Head Louvre Anthracite 24W 2CCT 3Hr EM	1092lm 1482lm 1870lm		14W 19W 24W	78 lm/w

Product Information

Warranty	5 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	3000K 4000K
IP Rating	IP65
IK Rating	IK08
Voltage	120-277V
Material (Body/Housing)	Aluminium
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >70

Colour Finish	Anthracite RAL7016
LED Life Expectancy	L70B50 54,000 Hours
Power Factor	0.9
Frequency	50/60Hz
Driver Type	Fixed
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-0°C to 40°C
EM Working Temperature	0°C to 40°C



GUARD BOLLARD

ARCHITECTURAL BOLLARDS

Packaging Information

Dimensions (mm)	L: 210 X W: 160 Ø
Product Net Weight (kg)	2.7 kg
Barcode	5055807629386
Box Dimensions (mm)	L: 205 x W:205 x D: 345 mm

Box Gross Weight (kg)	3.06 kg
Units/Outer Carton	1
Outer Carton Dimensions (mm)	L: 430 x W: 430 x D: 365 mm

