

Rotary Hammer XGT®

HR003G

40V max • SDS-PLUS • 28 mm •
2.8 J

Powerful three-action hammer with vibration damping

Efficient combination hammer HR003G delivers high power for professional work. The tool is lightweight and the tool balance is redesigned for increased operability. HR003G is equipped with Anti vibration technology (AVT). The machine can also be connected to the DX12 dust extractor system.



Technical specifications

Nominal Battery Voltage	40 V
Voltage XGT	✓
Brushless Motor	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 980 min ⁻¹
Impacts per Minute (IPM)	0 - 5000 min ⁻¹
Max. Drilling Diameter in Wood	32 mm
Max. Drilling Diameter in Concrete	28 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	10 - 18 mm
Impact Energy	2,8 J
Drilling diameter with TCT core bit	54 mm
Electronic brake	✓
Sound Power Level (L _{WA})	103 dB(A)

User benefits

- Battery protection circuit protects against overloading, over-discharging and over-heating
- AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- Low power consumption thanks to brushless motor
- Impact drilling, non-impact drilling and spike function
- Constant speed control automatically applies additional power to the motor to maintain speed under load to complete the most challenging jobs

Link to product - www.makita.com



Related products

Optional AC

191E54-9

Dust Collection System DX12



198993-4

Grease vessel for bit 100 ml



331886-4

Depth Gauge



821552-6

Makpac case (4)



835C84-5

Makpac Inner Tray Type 4



Other

[User manual](#)

[Parts drawing](#)