

Rotary Hammer Brushless XGT®

HR010GZ01

40Vmax, SDS-PLUS, 20 mm, 2.1J

Model HR010G is a 20mm SDS-PLUS combination hammer powered by 40Vmax XGT® Li-Ion battery.



Technical specifications

Vibration Level, Hammer Drilling Into Concrete	10,0 m/s ²
Vibration Uncertainty (K Factor), Hammer Drilling Into Concrete	1,7 m/s ²
Vibration Uncertainty (K Factor), Chiselling	1,5 m/s ²
Voltage XGT	✓
Nominal Battery Voltage	40 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1350 min ⁻¹
Impacts per Minute (IPM)	0 - 5000 min ⁻¹
Max. Drilling Diameter in Wood	26 mm
Max. Drilling Diameter in Concrete	20 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	6 - 14 mm
Impact Energy	2,1 J

User benefits

- Built-in LED light illuminates the work area
- Battery protection circuit protects against overloading, over-discharging and over-heating
- Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth

EAN 0088381782135

Link to product - www.makita.com



Related products

■ Standard AC

413N42-3
DEPTH GAUGE

821552-6
Маkpac case (4)



■ Other

User manual

Parts drawing