

PROGUARD Window Tape 50mm x 55m



Product Code	Pricing Unit	Colour	Size	Pack Quantity	Pallet Quantity
UVX10	Each	RED	50mm x 55m	24	480

Product Description:

UVX10 is a 135-micron strong and conformable polyethylene red or white film tape, coated with a high tack, removable, acrylic adhesive. The product exhibits excellent adhesion to a range of substrates and is particularly designed for rough and embossed surfaces. UVX10 additionally has excellent UV resistance, allowing it to be used for a range of temporary masking, protection, and external applications.

Benefits:

- Conformable and flexible for use around irregular surfaces
- Good initial tack for instant bonding and ultimate adhesion to a wide range of surfaces
Removes cleanly, without messy adhesive after use, for up to 6 months
- Thick and robust film allowing good protection against mechanical damage
- Performs well over a range of environmental conditions
- Excellent UV performance for up to 6 months
- Colour options allow good visibility for end users in application
- Can be applied manually or automatically, with no stretching of PE film
- Tearable by hand for ease of use
- High humidity resistance

Limitations:

- For extra sensitive surfaces use *Proguard Ultra Low Tack Tape*.

Application:

Temperature: between -20°C and + 70°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface to keep full adhesive performance. Recommended minimum application temperature +10°C. Pressure sensitive adhesive must be applied with a maximum of pressure to achieve maximum pressure level. Apply the tape by hand or with a *Proguard Tape Applicator*.

Performance Data:

Adhesive	Acrylic
Carrier	PE film
Total Thickness	0.135 ±0.05mm
Adhesion to Steel	≥2.6N/cm
Tensile Strength	≥19N/cm
Elongation	≥400
Service temperature range	-20°C -> + 70°C