



Applications

Framing, decking, furniture frames, furring, roof deck, sidewall sheathing, subflooring, window units, crate and box assembly, boxes, crates, pallets and pallet repair.

Features & Benefits


- Adjustable power - can increase up to 20% for the toughest drives
- Rugged construction - durable driver and carbide guidebody insert take a pounding
- Fast - up to 15 staples per second
- Adjustable depth-of-drive control for proper staple set
- Drives 16 ga. N staples from 32mm to 63mm
- EZ-clear latch provides quick and easy clearing of occasional jams
- Top loading, easy release feed system with reload indicators
- Adjustable exhaust directs exhaust air in any direction

Heavy wire stapler

Technical specifications

| | |
|------------------------------------------|----------------------|
| Dimension (LxWxH) | 365x92x305 mm |
| Net weight | 2,7 kg |
| Firing mode | Dual |
| Air inlet | 3/8" female NPT |
| Operating pressure | 5,5 - 8,3 bar |
| Air consumption (at 60 shots per minute) | 185 l/m |
| Operating temperature range | -18 - 49 °C |
| Sound pressure level (Lpa) | 93 dB |
| Sound power level (Lwa) | 99 dB |
| Vibration level | 3,1 m/s ² |
| Shots / second | 15 |
| Magazine capacity | 160 pieces |
| Gauge | 16 ga. |
| Collation type 1 | Glue collated |
| Collation angle | 0 ° |

Fastener specification



Description

SNS50XP-N, hw stapler, dual

Art. Nr.

XL3057

EAN code

8715274018393