



## SAFETY DATA SHEET

### CEMENTONE FAST-CURE PRIMER FOR ROOFS

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	CEMENTONE FAST-CURE PRIMER FOR ROOFS
PRODUCT NO.	14974
SUPPLIER	BOSTIK LIMITED COMMON ROAD STAFFORD STAFFORDSHIRE ST16 3EH +44 1785 272625 sds.uk@bostik.com

#### 2 HAZARDS IDENTIFICATION

Flammable. Harmful by inhalation and in contact with skin. Irritating to skin.

CLASSIFICATION (1999/45) Xn;R20/21. Xi;R38. R10.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
XYLENE	215-535-7	1330-20-7	30-60%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases is Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### INHALATION

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention.

##### INGESTION

DO NOT induce vomiting. Get medical attention immediately.

##### SKIN CONTACT

Remove excess material using a paper towel. Wash skin thoroughly with soap and water for several minutes. Get medical attention if irritation persists after washing.

##### EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Use: Foam. Powder.

##### SPECIFIC HAZARDS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

#### 6 ACCIDENTAL RELEASE MEASURES

##### PERSONAL PRECAUTIONS

Avoid skin and eye contact. Ensure adequate ventilation. Wear personal protective equipment. Wear self contained breathing apparatus.

##### ENVIRONMENTAL PRECAUTIONS

Prevent entry into drains and water courses.

##### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb onto sand, earth or absorbent granules. Pick up with non-sparking tools and place into metal containers with sealable lids. Mark containers with details of hazards and store in designated area ready for disposal.

#### 7 HANDLING AND STORAGE

## CEMENTONE FAST-CURE PRIMER FOR ROOFS

### USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Provide good ventilation.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

### STORAGE CLASS

Flammable liquid storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level.

### ENGINEERING MEASURES

Well-ventilated area.

### RESPIRATORY EQUIPMENT

Respiratory protection must be used if air contamination exceeds acceptable level. Wear mask supplied with: Gas cartridge suitable for organic substances.

### HAND PROTECTION

Protective gloves must be used if there is a risk of direct contact or splash. Use protective gloves made of: Nitrile. Use thin cotton gloves inside the rubber gloves if allergy risk.

### EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Black
ODOUR	Petroleum. Solvent.
SOLUBILITY	Insoluble in water
RELATIVE DENSITY	0.9
FLASH POINT (°C)	25

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions. Avoid: Heat, sparks, flames.

### CONDITIONS TO AVOID

Avoid contact with strong oxidisers.

### HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## 11 TOXICOLOGICAL INFORMATION

## CEMENTONE FAST-CURE PRIMER FOR ROOFS

### INHALATION

Harmful by inhalation.

### INGESTION

May cause discomfort if swallowed. May cause stomach pain or vomiting.

### SKIN CONTACT

Harmful in contact with skin. Irritating to skin.

### EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

Not regarded as dangerous for the environment. However, contamination of the aquatic or terrestrial environments should be avoided

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

This material is classified as special waste as defined by Special Waste Regulations 1996 and must be disposed of by an authorised contractor

### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

## 14 TRANSPORT INFORMATION



PROPER SHIPPING NAME	PAINT RELATED MATERIAL
ENVIRONMENTALLY HAZARDOUS SUBSTANCE/MARINE POLLUTANT	No.
UN NO. ROAD	1263
ADR CLASS NO.	3
ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III
TUNNEL RESTRICTION CODE	(D/E)
HAZARD No. (ADR)	30
ADR LABEL NO.	3
HAZCHEM CODE	•3YE
UN NO. SEA	1263
IMDG CLASS	3
IMDG PACK GR.	III
EMS	F-E, S-E
UN NO. AIR	1263
AIR CLASS	3
AIR PACK GR.	III

## 15 REGULATORY INFORMATION

### LABELLING



Harmful

## CEMENTONE FAST-CURE PRIMER FOR ROOFS

CONTAINS XYLENE

### RISK PHRASES

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R38	Irritating to skin.

### SAFETY PHRASES

S2	Keep out of the reach of children.
S13	Keep away from food, drink and animal feeding stuffs.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.

### STATUTORY INSTRUMENTS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

### APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

### GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

## 16 OTHER INFORMATION

### GENERAL INFORMATION

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

### INFORMATION SOURCES

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

### REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision. This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

### ISSUED BY

Approved LJ

REVISION DATE July 2009

REV. NO./REPL. SDS GENERATED 2

DATE August 2007

### RISK PHRASES IN FULL

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R38	Irritating to skin.