

Toughsheet Building Products Bespoke Data Sheet

Manufacturer/ Supplier

- Frank Mercer & Sons
Chequerbent Works
Westhoughton
Bolton
BL5 3JF

Product Out-line

- Recycled Polythene Sheeting for General purpose use

Dimension and Tolerance

- Manufactured to Nominal
Tolerances - Length - +/- 10%
Width - +/- 10%
Thickness - +/- 10%
Elongation - + 400%
Appearance - May contain particles/
streaks, but holes are absent in film



Storage

- Good code of practice must be used;
Store in horizontal position not in direct sun light.

N/B - sun Light (UV) may degrade this product

COSHH

- Toxicity - LD Polythene are chemically non-reactive, biologically inert and can be regarded as harmless
- Static - Polythene can acquire static electrical charges. Sparks are potentially dangerous in areas where flame or explosion hazards exist.
- Skin Contact - No special measures
- Eye contact - No special measures
- Inhalation - No special measures
- ingestion - No special measures

Fire Resistance

Extinguishing media

- Use Dry Powder

Unsuitable Extinguishing

- Do not use direct water jets in the early stages of extinguishing a fire as this may help to spread the flames. Do Not use water extinguishers in close proximity to live electrical installations.

Fire fighting

- Seek advice from local Fire Authority



Disposal Of Product

- Through normal trade waste outlets. F Mercer & Sons are a fully licensed Re-cycler and will recycle any polythene in line with the department of environment guidelines and standards.

