

TWIN BARREL FOOT PUMP

MODEL NO: FP6.V2

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



instructions

1. SAFETY

1.1. BEFORE YOU BEGIN

The device is designed for inflating car, motorbike and bicycle tyres and could be used for inflatables given the right connector. Generally acknowledged accident prevention regulations and enclosed safety instructions must be observed. Only perform work described in these instructions for use. Any other use is improper. The manufacturer will not assume responsibility for damage resulting from such use.

1.2. GENERAL SAFETY INSTRUCTIONS

protection

- ✓ To operate this device safely, the user must have read and understood these instructions for use before using the device for the first time.
- ✓ Observe all safety instructions. Failure to do so may cause harm to you and others.
- ✓ Retain these instructions for future reference.
- ✓ If the product is rendered defective it must either be professionally repaired or taken out of service.
- \checkmark Keep the device out of the way of children and other unauthorised persons.
- **× DO NOT** overload the device.
- * DO NOT use the device for purposes for which it is not intended.
- Exercise caution and only work when in good condition. DO NOT use if you are tired, ill, ingested alcohol, medication or drugs.
- * This product is **NOT** intended to be used by persons (including children) or who are limited in their physical, sensory or mental capacities or who lack experience and/or knowledge of the product unless they are supervised, or have been instructed on how to use the product, by a person responsible for their safety.
- ✓ Always comply with all applicable domestic and international safety, health, and working regulations.

1.3. DEVICE-SPECIFIC SAFETY INSTRUCTIONS

- The gauge should be used as an indication of pressure only. We recommend the use of a dial pressure gauge for definitive reading.
- ✓ Make sure you are positioned firmly and with a natural stance when working with the device.
- ✓ Only work with good light and visibility.
- \checkmark Children should be supervised to ensure that they **DO NOT** play with the device.
- ✓ Information on the device that is no longer legible must be replaced immediate.

2. INTRODUCTION

High power, steel framed foot pump with two Ø44 x 110mm aluminium barrels. Ø75mm dial type pressure gauge calibrated in psi and bar and ranges from 0-160psi and 0-10bar. Suitable for Presta and Schrader valve. Fitted with 650mm flexible pressure hose with locking connector. Fitted with safety locks for security.

3. SPECIFICATION

MODEL NO:	FP6.V2
Gauge Range	0-160psi
Max. Output Pressure:	120psi
Nett Weight:	1.56kg
Pressure Units:	Bar, psi



4. OPERATION

- 4.1. To start using the foot pump, first release the safety locks on each side (Fig.1). Allow the foot pad to slowly rise.
- 4.2. Place the foot pump on a level, stable surface.
- 4.3. The connector has both Shrader (marked S) or Presta (marked P) valves . Apply appropriate connector to the valve of the tyre to be inflated and then lock with locking lever ((Fig.2)..



- 4.4. If you are working with any of the supplied ball spike or inflatables adapter (Fig.4) insert the desired adapter into the larger Schrader connector port and close the locking lever down (fig.1). Insert the other end of the adapter into the inflation orifice of the object to be inflated.
- 4.5. Observe gauge and pump evenly with moderate force and allow it to slowly return. Pump until the desired pressure is reached.
- 4.6. After the pump has been used compress the foot pump and lock.

5. MAINTENANCE

- Transport in original packaging.
- \checkmark Keep the tyre pump clean by wiping with a damp cloth.
- DO NOT allow water ingress into the tyre pump.
- **x DO NOT** use solvents to clean the tyre pump.
- ✓ Store the tyre pump in a well ventilated and dry childproof area.
- 5.1. LIFE TIME OF THE MACHINE/DISPOSAL

Through years of normal wear, the tyre pump will eventually become unserviceable. When this happens ensure that it is disposed of in accordance with local authority regulations.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR 01284 757500 @ sales@sealey.co.uk @ www.sealey.co.uk