Section 1. Product and Company Identification.

1.1 Model Number; SCS271 v1

1.2 Description; Stud Lock High Strength 50ml Pack of 12



Sealey Group. Kempson Way, Bury St. Edmunds, Suffolk. IP32 7AR

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 10 February 2015





Section 2. Hazards Identification.

2.1 Classification of the substance or mixture.

EUH208: Contains 1-acetyl-2-phenylhydrazine. May produce an allergic reaction.

2.2 Label elements.

Hazard pictogram(s)





Signal Word. Warning. Environmentally Hazardous

Hazard statements;

EUH208 Contains 1-acetyl-2-phenylhydrazine. May produce an allergic reaction.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements;

P102 Keep out of reach of children.

P264 Wash contaminated skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor if you feel unwell.

P321 Specific treatment (see information on this label).

2.3 Other hazards.

None identified.



Section 3. Substances.

			Classification	
3.1 Chemical Name (substance)	3.1 CAS No.	3.2 Concentration Weight	Hazard Class & Category Code	Hazard Statements ¹
Polyglycol Dimethacrylate	109-16-0	50 - 70%	-	-
2-Hydroxypropyl Methacrylate	923-26-2	1 - 10%	Eye Irrit. 2	H319
			Skin Sens. 1	H317
Acrylic Acid	79-10-7	1 - 10%	Flam. Liq. 3	H226
			Acute Tox. 4	H332
			Acute Tox. 4	H312
			Acute Tox. 4	H302
			Skin Corr. 1A	H314
			Aquatic Acute 1	H400
Cumene Hydroperoxide	80-15-9	1 - 10%	Org. Perox. E	H242
			Acute Tox. 3	H331
			Acute Tox. 4	H312
			Acute Tox. 4	H302
			STOT RE 2	H373
			Skin Corr. 1B	H314
			Aquatic Chronic 2	H411
1-Acetyl-2-Phenylhydrazine	114-83-0	< 1%	-	-
N,N-Dimethyl-P-Toluidine	99-97-8	< 1%	Acute Tox. 3	H331
			Acute Tox. 3	H311
			Acute Tox. 3	H301
			STOT RE 2	H373
			Aquatic Chronic 3	H412

¹For full text Statements, see Section 16.



Section 4. First Aid Measures.

4.1 Description of first aid measures

Inhalation

Remove casualty from exposure ensuring one's own safety whilst doing so. Get medical attention if any discomfort continues.

Skin Contact

Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Rinse with water. Get medical attention if any discomfort continues

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if any discomfort continues

Ingestion

Wash out mouth with water.
Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact There may be irritation and redness at the site of contact.

Eye contact There may be irritation and redness. The eyes may water profusely. **Ingestion** There may be soreness and redness of the mouth and throat.

Inhalation There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause

coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed Eye bathing equipment should be available on the premises.

Section 5. Fire Fighting Measures.

5.1. Extinguishing media

Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Wear self-contained breathing apparatus.

Wear protective clothing to prevent contact with skin and eyes.



Section 6. Accidental Release Measures.

6.1. Personal precautions, protective equipment and emergency procedures

If outside do not approach from downwind.

If outside keep bystanders upwind and away from danger point.

Mark out the contaminated area with signs and prevent access to unauthorised personnel.

Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Do not discharge into drains or rivers.

Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Absorb into dry earth or sand.

Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

See Section 7 for information on Safe Handling

See Section 8 for information of Personal Protective Equipment.

See Section 13 for information on disposal.

Section 7. Handling and Storage.

7.1. Precautions for safe handling

Avoid direct contact with the substance.

Ensure there is sufficient ventilation of the area.

Do not handle in a confined space.

Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Store in cool and well ventilated area.

Keep container tightly closed.

7.3. Specific end use(s)

Intended for use as Stud Lock High Strength: Model Number identified in 1.1 with Description stated in 1.2.



Section 8. Exposure Controls/Personal Protection.

8.1. Control parameters

P264: Wash contaminated skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor if you feel unwell.

P321: Specific treatment (see information on this label).

S2: Keep out of the reach of children.

S24: Avoid contact with skin.

S37: Wear suitable gloves.

S46: If swallowed, seek medical advice immediately and show this container or label.

Hazardous Ingredients:

ACRYLIC ACID

Workplace exposure limits: Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	30mg/m ³	60mg/m ³	-	-

8.2. Exposure controls

Appropriate Engineering Controls

Ensure there is sufficient ventilation of the area.

Eye/Face Protection

Safety glasses with side shields or chemical safety goggles.

Ensure eye bath is to hand.

Skin Protection

EN 374 Chemical resistant protective gloves.

Wear suitable protective clothing.

Respiratory Protection

Self-contained breathing apparatus must be available in case of emergency.



Section 9. Physical and Chemical Properties.

9.1. Information on basic physical and chemical properties

The following information is not a technical specification or sales specification.

(a) Appearance: Red liquid.

(b) Odour:

(c) Odour threshold;

(d) pH:

Barely perceptible.

No data available.

No data available.

(e) Melting point/freezing point; >35°C (f) Initial boiling point and boiling range; >93°C

(g) Flash point;
No data available.
(h) Evaporation rate;
No data available.
(i) Flammability (solid, gas);
No data available.
(j) Upper/lower flammability or explosive limits;
No data available.
(k) Vapour pressure;
No data available.
(l) Vapour density;
No data available.

(m) Relative density; 1.1

(n) Solubility(ies);
(o) Partition coefficient: n-octanol/water;
(p) Auto-ignition temperature;
(q) Decomposition temperature;
(r) Viscosity;
(s) Explosive properties;
(t) Oxidising properties.
No data available.
No data available.
No data available.

9.2 Other information No data available.

Section 10. Stability and Reactivity.

10.1. Reactivity Stable under recommended transport or storage conditions.

10.2. Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions Hazardous reactions will not occur under normal transport

or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid Heat.

10.5. Incompatible materials10.6. Hazardous decomposition productsStrong oxidising agents. Strong acids.Emits toxic fumes during combustion

LD50



mg/kg

Section 11. Toxicological Information.

MUS

11.1. Information on toxicological effects

Hazardous Ingredients:

ORL

2-HYDROXYPROPYL METHACRYLATE

ACRYLIC ACID				
IPR	RAT	LD50	22	mg/kg
ORL	MUS	LD50	830	mg/kg
ORL	RAT	LD50	1250	mg/kg
SCU	MUS	LD50	1590	mg/kg

7964

CUMENE HYDROPEROXIDE

ORL	MUS	LDLO	5	mg/kg
ORL	RAT	LD50	382	mg/kg
SCU	RAT	LD50	382	mg/kg

N,N-DIMETHYL-P-TOLUIDINE

IPR	MUS	LD50	212	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT INH DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Opt - Optical

Inh - Inhalation

Drm - Dermal

Symptoms / routes of exposure

Skin contact There may be irritation and redness at the site of contact.

Eye contact There may be irritation and redness. The eyes may water profusely. **Ingestion** There may be soreness and redness of the mouth and throat.

Inhalation There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause

coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.



Section 12. Ecological Information.

12.1. Toxicity
12.2. Persistence and degradability
12.3. Bioaccumulative potential
12.4. Mobility in soil
No data available.
No data available.
No data available.

12.5. Results of PBT and vPvB assessment This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects No data available.

Section 13. Disposal Considerations.

13.1. Waste treatment methods

Dispose of in accordance with local authority regulation.

Section 14. Transport Information.

ADR. International Carriage of Dangerous Goods by Road.

14.1. UN number UN 3082

14.2. Name and Description Environmentally hazardous substance, liquid, n.o.s

(Cumene Hydroperoxide)

14.3. Transport hazard class(es) 9 **14.4.** Packing group III

14.5. Environmental hazards Toxic to aquatic life with long lasting effects.

14.6. Special precautions for user No special precautions necessary.

IATA. International Air Transport Association.

14.1. UN number UN 3082

14.2. UN Proper Shipping Name/Description Environmentally hazardous substance, liquid, n.o.s.

(Cumene Hydroperoxide)

14.3. Transport hazard class(es) 9 **14.4.** Packing group III

14.5. Environmental hazards Toxic to aquatic life with long lasting effects.

14.6. Special precautions for user No special precautions necessary.

IMDG. International Maritime Dangerous Goods.

14.1. UN number UN 3082

14.2. UN proper shipping name Environmentally hazardous substance, liquid, n.o.s

(Cumene Hydroperoxide)

14.3. Transport hazard class(es) 9 **14.4.** Packing group III

14.5. Environmental hazards Toxic to aquatic life with long lasting effects.

14.6. Special precautions for user No special precautions necessary.

14.7. Transport in bulk – Maritime only. Bulk transport is not applicable to this product



Section 15. Regulatory Information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture No data available.

15.2. Chemical safety assessment No data available.

Section 16. Additional Information.

Full text of Phrases and Statements used in Section 3;

H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

The above information is believed to be accurate and represents the best information currently available.

No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their

particular purpose.

Issue level	Date	Revisions
1	08/04/2016	First issue.
2	22/03/2017	Format only.
3	26/06/2017	Section 14
4	15/05/2019	Section 2
5	27/03/2024	Format
6	10/07/2024	Section 2.2

End of Safety Data Sheet.