MIG

## Order Code: JA-200PFC









## **Key Features**

- IGBT Inverter technology for the professional user
- MMA/DC Lift TIG
- Wide input voltage 95-265V
- Hot start ignition, anti stick
- 33 Khz inverter frequency, high-efficiency
- Self adaptive arc force
- Compact size, lightweight and modern design
- Heavy duty 35-50mm dinse sockets
- Easy arc starting, minimal spatter
- Stable and reliable arc
- Auto-compensation for voltage fluctuation
- Advanced single PCB construction
- Generator friendly\*\*
- Can weld electrodes of up to 4mm

## Technical Data

Input Voltage	95-265V - AC 50/60Hz	
	115V	230V
leff(A)	13.4	12.7
Input Power (kVA)	3.5	7.2
Current Range (A)	10 - 110	10 - 200
Duty Cycle @ 40°C	110A @ 25%	200A @ 25%
No-Load Voltage (V)	68	
Efficiency (%)	85	
Power Factor	0.998	
Protection/Insulation Class	IP21S/F	
Dimensions (LxWxH mm)	365 x 135 x 280	
Weight (Kg)	6.4	
Efficiency (%) Power Factor Protection/Insulation Class Dimensions (LxWxH mm)	85 0.998 IP21S/F 365 x 135 x 280	

<sup>\*5</sup> year warranty subject to product registration \*\*Generators should have regulated output







Site Bag Order Code: JSB-01



Shoulder Strap Order Code: JSS-01



 High quality tactile rubber finish to mouldings & handle

The power in inverter technology

Innovative welding technology

ACCESSORIES