

Mobile access steps with platform, single-sided access, with steel open-grid treads and platform

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.

Product description

- Quick and easy assembly thanks to the new connecting elements.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Maximum loading capacity 150 kg.



Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.
Complies with EN 131-7

Product features

Coating: natural
 Connection Stile-Rung: welded
 Guardrail height: 1000 m
 Load: max. 150 kg
 Material: Aluminum/steel, galvanised
 Pitch rung/tread: 240 mm
 Platform length: 800 mm
 Platform width: 600 mm
 Standards: EN 131-7
 Tread depth: 200 mm
 Type rung/tread: Open-grid surface
 Warranty: 10 years

Product variants

Order number	Base	Number of rungs, incl. platform	Platform height	Transport dimensions	Weight	Working height
41951	0,77 m × 1,27 m	3	0.72 m	1.150 mm × 780 mm × 350 mm	41.5 kg	2.7 m
41952	0,82 m × 1,45 m	4	0.96 m	1.350 mm × 830 mm × 410 mm	47.5 kg	2.95 m
41953	0,87 m × 1,63 m	5	1.2 m	1.500 mm × 890 mm × 410 mm	53.6 kg	3.2 m
41954	0,93 m × 1,81 m	6	1.44 m	1.820 mm × 930 mm × 350 mm	59.7 kg	3.45 m
41955	0,98 m × 1,99 m	7	1.68 m	1.920 mm × 990 mm × 350 mm	66 kg	3.7 m
41956	1,03 m × 2,17 m	8	1.92 m	2.220 mm × 1.130 mm × 350 mm	72.9 kg	3.9 m